

# 101 PE

## Non-migrating Slip Agent

### Supplied in shape of:

Mixture, Flakes.

### Active agent:

Non-migrating slip and demoulding additive.

### Area of use:

**HECO®SLIP 101 PE** is suitable for processing polyethylene, polypropylene and polyamide in injection moulding and extrusion.

### Recommended dose:

**HECO®SLIP 101 PE** is added in the range of 1.0 – 5.0 % depending on the desired properties. We recommend an addition of min. 1.0 – 2.0 %.

### Properties:

**HECO®SLIP 101 PE** is a non-migrating internal slip agent and increases the flow ability of the polymer melt. This facilitates the mould filling and demoulding properties.

### Pallet size:

1000.0 kg (50 Sack á 20.0 kg) / Pallet, net.

### Safety Precautions

#### Foodstuff regulation:

Approval according to EU (VO) No. 10/2011.

Approval according to the US FDA, see "Food Contact Approvals".

#### Storage:

No reduction in quality has been reported when properly stored under normal room conditions up to twelve (12) months.

#### Handling:

The precautions and hygienic measures usual in the handling of any chemical product should be observed.

#### In case of fire:

In case of fire, suitable extinguishers are aqueous spray, foam or dry chemical; a full jet of water is unsuitable.

**HECOPLAST®** and **HECO®** are registered trademarks

Our information is based on the most careful analysis, nevertheless these are not guaranteed product features.  
Specific field tests are being recommended under any circumstance.

**HECOPLAST®** GmbH Kunststoffadditive, Zollhausstrasse 24, D - 58640 Iserlohn Telephone + 49 2371 / 797 61-0 – E-Mail: [info@hecoplast.de](mailto:info@hecoplast.de)