

# 150 PE

## Slip and anti-blocking agent in PE

### Supplied in shape of:

Mixture, Granule

### Active agent:

Slip and anti-blocking agent on a polyethylene carrier.

### Area of use:

**HECO<sup>®</sup>SLIP 150 PE** is suitable for processing polyethylene and polypropylene in injection moulding and extrusion.

### Recommended dose:

**HECO<sup>®</sup>SLIP 150 PE** is added in the range of 1.5 – 10 % depending on the desired properties. We recommend an addition of at least 1.5 – 3.5 %.

### Properties:

**HECO<sup>®</sup>SLIP 150 PE** is an external slip agent which reduces friction and blocking/adhesion of the mixture during the mixing process. It migrates quickly to the surface and forms a release film with good sliding and anti-blocking properties.

### Pallet size:

1000.0 kg (50 sacks at 20.0 kg) / pallet, net.

### Safety Precautions

#### Foodstuff regulation:

Approval according to EU (VO) No. 10/2011.

Specific migration limit: 60 mg/kg food (10 mg/dm<sup>2</sup>).

Approval according to the US FDA, see "Food Contact Approvals".

In accordance with European Pharmacopoeia 11th edition 2023.

#### Storage:

No reduction in quality has been reported when properly stored under normal room conditions up to twelve (12) months.

#### Handling:

The precautions and hygienic measures usual in the handling of any chemical product should be observed.

#### In case of fire:

In case of fire, suitable extinguishers are aqueous spray, foam or dry chemical; a full jet of water is unsuitable.

**HECOPLAST<sup>®</sup>** and **HECO<sup>®</sup>** are registered trademarks

Our information is based on the most careful analysis, nevertheless these are not guaranteed product features.  
Specific field tests are being recommended under any circumstance.

**HECOPLAST<sup>®</sup>** GmbH Kunststoffadditive, Zollhausstrasse 24, D - 58640 Iserlohn Telephone + 49 2371 / 797 61-0 – E-Mail: [info@hecoplast.de](mailto:info@hecoplast.de)