

# 210 PE

**Amine-free short-term antistatic agent**

**Supplied in shape of:**

Mixture, Granule

**Active agent:**

Amine-free short-term antistatic agent on a polyethylene carrier.

**Area of use:**

**HECO<sup>®</sup>STAT 210 PE** is suitable for processing polyolefins such as polyethylene and polypropylene in film production and injection moulding/extrusion applications.

**Recommended dose:**

**HECO<sup>®</sup>STAT 210 PE** is added in the range of 1.0 - 3.0 % depending on the desired properties.

**Properties:**

**HECO<sup>®</sup>STAT 210 PE** is an internal short-term antistatic agent whose non-polar residues protrude into the polymer matrix and polar residues from the surface into the air. Due to the polar properties, the polar groups have a certain affinity to humidity. This forms a thin film in which the charge can flow off through ionic conduction.

**Pallet size:**

1000.0 kg (50 sacks at 20.0 kg) / pallet, net.

**Safety Precautions**

**Foodstuff regulations:**

Approval according to EU (VO) No. 10/2011.

Specific migration limit: 60 mg/kg food (10 mg/dm<sup>2</sup>).

Approval according to the US FDA, see "Food Contact Approvals".

**Storage:**

No reduction in quality has been reported when properly stored under normal room conditions up to twelve (12) months.

**Handling:**

The precautions and hygienic measures usual in the handling of any chemical product should be observed.

**In case of fire:**

In case of fire, suitable extinguishers are aqueous spray, foam or dry chemical; a full jet of water and CO<sub>2</sub> are unsuitable.

**HECOPLAST<sup>®</sup>** and **HECO<sup>®</sup>** are registered trademarks

Our information is based on the most careful analysis, nevertheless these are not guaranteed product features.  
Specific field tests are being recommended under any circumstance.

**HECOPLAST<sup>®</sup>** GmbH Kunststoffadditive, Zollhausstrasse 24, D - 58640 Iserlohn Telephone + 49 2371 / 797 61-0 – E-Mail: [info@hecoplast.de](mailto:info@hecoplast.de)