

231 PO

Long-term antistatic

Supplied in shape of:

Mixture, Granule.

Active agent:

Long-term antistatic agent.

Area of use:

HECO[®]STAT 231 PO is suitable for processing PVC, TPU and TPE.

Recommended dose:

HECO[®]STAT 231 PO is added in the range of approx. 1% depending on the desired properties.

Properties:

HECO[®]STAT 231 PO forms a self-organizing, dissipative structure on the product surface. In this way, static charges are discharged. The anti-static effect is maintained over a long period of time.

Pallet size:

1000.0 kg (50 Sack á 20.0 kg) / pallet, net.

Safety Precautions

Foodstuff regulations:

On demand.

Storage:

Appropriate storage under normal conditions.

Handling:

The precautions and hygienic measures usual in the handling of any chemical product should be observed.

In case of fire:

In case of fire, suitable extinguishers are water mist, foam, CO₂ or dry chemical, a full jet of water are unsuitable.

HECOPLAST[®] and **HECO[®]** are registered trademarks

Our information is based on the most careful analysis, nevertheless these are not guaranteed product features.
Specific field tests are being recommended under any circumstance.

HECOPLAST[®] GmbH Kunststoffadditive, Zollhausstrasse 24, D - 58640 Iserlohn Telefon + 49 2371 / 797 61-0 — E-Mail: info@hecoplast.de